

ECLIPSE

DP2 Saturation Diving Vessel

"On a Mission to Incident and Injury Free"



VESSEL IDENTIFICATION

Port of Registry	Nassau
Flag	Bahamian
Class	Dual class DNVDYNPOSAUTR and IRS

ACCOMMODATIONS

Berths	107
--------	-----

DIMENSIONS

Overall length	112m
Beam	20.5m
Max. speed	12 knots
Service speed	10 knots
Displacement	9,909 T
Operating draft	6.0m - 6.4m
Clear deck area	800m ²
Deck load	5 T/m ²
Gross tonnage	7,114 T
Net tonnage	2,134 T
Power supply total	12,750 kW

CAPACITIES

Fuel oil	3,664m ³
Fresh water	325m ³
Fresh water plant	2 x 7.1 T/day
RO plant	15m ³ (total 29m ³)
Bollard pull	96 T
Lube oil	28m ³

HELIDECK

"D" value	22.2m
-----------	-------

DYNAMIC POSITIONING (DP) SYSTEM

Kongsberg SDP21 duplex Reference System
3 x DGPS MultiFix Seapos + spare
1 x Artemis interface
1 x HIPAP 350
1 x Simrad HPR-410
2 x Bandak Mk15b
1 x MDL Fan Beam Laser Mk IV

MAIN PROPULSION AND THRUSTERS

Type	Self-propelled, DP
Stern thrusters	2 x Kamewwa azimuth 1,500 BHP, 20T thrust each
Bow thrusters	2 x Kamewwa tunnel 1,500 BHP, 16T thrust each
Main engines	5 x NOHAB F216V 2650kW
Main	1 x Kamewwa 6,000 BHP, 56T thrust

CRANES

Main	Hydramarine HMC 3568 LKO 250-32
Type	AHC Deck Knuckle Jib
Main Capacity	150T @ 10m (double line); 100T @ 15m (single line);
A-frame	20T @ 8m over stern hydraulic
Auxiliary	Hydraulic A Frame aft 20T at 9.8m
Midships	Maritime Hydraulics MH 802
Capacity	4.3MT @ 26m

SATURATION DIVING SYSTEM

Built to IMCA standards and certified by the DNV, 16 man split level diving system with hyperbaric lifeboat	
Depth rating	200msw
Moonpool	Yes

LIFEBOATS/LIFE-RAFTS

2 x 60 person (TEMPSEC type) lifeboats
8 x 25 person life-rafts
4 x 20 person life-rafts
1 x 16-person hyperbaric lifeboat



Cal Dive International, Inc.
Corporate Office
2500 CityWest Blvd., Suite 2200
Houston, Texas 77042
877-361-2600
www.caldive.com